

EAN Code: 3606480088377

Price\*: 19.00 EUR



### Main

|                           |  |
|---------------------------|--|
| Range                     | Acti 9                                       |
| Product name              | Acti 9 iLL                                   |
| Product or component type | Modular pilot lighth                         |
| Device short name         | IIL  |
| [Us] rated supply voltage | 110...230 V AC at 50/60 Hz<br>110...130 V DC |

### Complementary

|  |   |
|--|---|
| Local signalling                                 | 2 LEDs green/red, service life 100000 h of constant lighting efficiency (consumption 0.6 W)   |
| Mounting mode                                    | Fixed   |
| Mounting support                                 | Symmetrical DIN rail  |
| Comb busbar and distribution block compatibility | Upside: ProDis  |
| 9 mm pitches                                     | 2   |
| Height   | 82 Mm   |
| Width  | 18 Mm   |
| Depth  | 69.5 Mm   |
| Colour   | White (RAL 9003)  |
| Auxiliary connection terminal                    | Tunnel type terminal 1 cable(s) rigid 0.5 mm <sup>2</sup><br>Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup><br>Tunnel type terminal 1 cable(s) flexible 0.5 mm <sup>2</sup><br>Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup><br>Tunnel type terminal 2 cable(s) flexible with ferrule 2.5 mm <sup>2</sup> |
| Wire stripping length                            | 9 Mm  |
| Tightening torque                                | 1 N.M   |

### Environment

|                         |               |
|-------------------------|---------------|
| Standards               | IEC 60947-5-1 |
| IP degree of protection | IP2<br>IPxx B |
| Pollution degree        | 2             |
| Tropicalisation         | 2             |
| Relative humidity       | 95 % at 55 °C |

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage   | -40...80 °C |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 45 G    |
| Package 1 Height             | 6.6 Cm  |
| Package 1 width              | 1.8 Cm  |
| Package 1 Length             | 8.2 Cm  |
| Unit Type of Package 2       | S03     |
| Number of Units in Package 2 | 108     |
| Package 2 Weight             | 5.91 Kg |
| Package 2 Height             | 30 Cm   |
| Package 2 width              | 30 Cm   |
| Package 2 Length             | 40 Cm   |
| Unit Type of Package 3       | BB1     |
| Number of Units in Package 3 | 12      |
| Package 3 Weight             | 602 G   |
| Package 3 Height             | 7.8 Cm  |
| Package 3 width              | 9.8 Cm  |
| Package 3 Length             | 23.3 Cm |

## Offer Sustainability

|                             |   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product   |
| REACH Regulation            | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>   |
| Mercury free                | Yes   |
| RoHS exemption information  | <a href="#">Yes</a>   |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>   |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free plastic parts & cables product   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**